

# OLAMEF

Electronic  
component preforming  
equipment



TOP ITALIAN MACHINE MANUFACTURER  
FOR ELECTRONIC INDUSTRY



# TP6/D

CUTTING AND BENDING MACHINE FOR AXIAL COMPONENTS WITH DELRIN TOOTHED DISCS NOT TO MARK LEADS

---

20.OL11 STANDARD

---

20.OL12 REINFORCED

---



# TP6/97

CUTTING AND BENDING MACHINE FOR AXIAL COMPONENTS WITH QUICK SET UP

---

---

20.OL01 /97 STANDARD

---

20.OL04 /97 REINFORCED

---

20.OL06 /97 REDUCED

---




This system automatically adjusts the bending wheels, reducing the set-up time and making it easier.

This system is available with the some versions of the TP6 machine. Warning= the maximum pitch possible with the /97 system is 40 mm and the maximum "B" is 10 mm

# STANDARD VERSIONS OF TP6, TP6/D AND TP6/97 MACHINES

20.OL01 - 20.OL11 - 20.OL01/97


TP6/1 STANDARD VERSION



	MM		IN	
	min	max	min	max
<b>P</b>	6,5	60	.255	2.362
<b>B</b>	4	13	.157	.511
<b>c</b>	1,2		.047	
<b>L</b>		50		1.968
<b>d</b>	0,4	1,3	.015	.051
<b>D</b>	0,4	16	.015	.629

20.OL04 - 20.OL12 - 20.OL04/97


TP6/4 EXTRA REINFORCED BENDIN



	MM		IN	
	min	max	min	max
<b>P</b>	10,16	60	.4	2.362
<b>B</b>	5	13	.196	.511
<b>c</b>	2,4		.094	
<b>L</b>		50		1.968
<b>d</b>	0,6	1,4	.023	.055
<b>D</b>	0,6	16	.023	.629

20.OL06 - 20.OL06/97


TP6/6 REDUCED BENDING – ADJUSTABLE PITCH



	MM		IN	
	min	max	min	max
<b>P</b>	6,08	60	.2	2.362
<b>B</b>	4	13	.157	.511
<b>c</b>	0,8		.031	
<b>L</b>		50		1.968
<b>d</b>	0,4	0,8	.015	.031
<b>D</b>	0,4	10	.015	.039

20.OL07 - 20.OL09 - 20.OL10

TP6/7 – TP6/9 – TP6/10 REDUCED BENDING FIX PITCH



	MM		IN	
	min	max	min	max
<b>B</b>	4	10	.157	.393
<b>c</b>	0,5		.018	
<b>d</b>	0,4	0,6	.015	.023
<b>D</b>	0,4	4	.015	.157

code 20.OL07	<b>P</b>	5,08	.2
code 20.OL09	<b>P</b>	7,62	.3
code 20.OL10	<b>P</b>	10,16	.4