

HAND SEALER

70-100-608x & 70-100-609x

Sealing arm made of plastic and body made of casting can bear up high temperature and impact. Casting body coated two times by insulating material protects from rust. Transformer, which is very important part in the middle of sealer functions, is made of the best quality coil and parts by Posteel®. By the heating element made of special nickel, chrome it promises a long-term use. All wires in the body and P.C.B are coated by insulating varnish, material especially like Epoxy. Cutter equipped on the sealing arm makes you easy when you work regardless film difference. Smaller size is easy to move so it can also be used in narrow place.



Product Specifications

TEMPERATURE OF SEALING	150 MAX
SEALING TIME	MIN 0.5 Sec- MAX 2.5 Sec
REGULAR SEALING TIME	1.5 Sec
LENGTH OF SEALING	From 200 to 400mm
WIDTH OF SEALING	From 2 to 5mm
POWER CONSUMPTION	950W
SEALING THICKNESS	0.5mm below
WEIGHT	From 3.3 to 5kg
MATERIAL FOR SEALING	PE, PP, LDPE, PVC

Part numbers

PART NUMBER	MODEL	LENGTH OF SEALING	WIDTH OF SEALING	CUTTER
70-100-6084	XP-200 /2	200MM	2MM	without cutter
70-100-6085	XP-300 /2	300MM	2MM	
70-100-6086	XP-400 /2	400MM	2MM	
70-100-6087	XP-200 /5	200MM	5MM	
70-100-6088	XP-300 /5	300MM	5MM	
70-100-6089	XP-400 /5	400MM	5MM	
70-100-6094	XP-200 /2C	200MM	2MM	with cutter
70-100-6095	XP-300 /2C	300MM	2MM	
70-100-6096	XP-400 /2C	400MM	2MM	
70-100-6097	XP-200 /5C	200MM	5MM	
70-100-6098	XP-300 /5C	300MM	5MM	
70-100-6099	XP-400 /5C	400MM	5MM	