

Electronic component preforming equipment









TOP ITALIAN MACHINE MANUFACTURER
FOR ELECTRONIC INDUSTRY





13.OLO1: 110 V 13.OLO2: 220 V



TP/TO-CF is an automatic machine designed to cut and form transistors in tube (TO-220, TO-218, TO-126). All strokes are controlled by a PLC. The complete operation is fully automatic and each form needs a dedicated die. Two wire holders lock the leads before the cutting forming operations. Special forms to customers specifications are available upon request.



PRODUCTION: 3000 P/H


STANDARD DIE ASSEMBLIES

131000 STRAIGHT CUT





MM			IN			
=7	min	max	fix	min	mex	fix
a	3	13		.118	.511	












	MM			IN		
П	min	FTESK	fix	min	max	fix:
а	2,5	В		.098	.314	
b*			2			078
C+			2.5			098




132100 CENTRAL LEAD SPREAD AND CUT



	MM			IN		
	min	max	fix.	min	max	fix
a	7	13	1110-11	.275	.511	
b	4	10		.157	.393	
c			1.4			.055
p*		- 3	2.54			.1

132200 center lead spread and lock





		MM			IN	
П	min	max	fox	min	max	fix
а	7	13	200 (17.00)	_275	.511	
ь	4	10		.157	.393	
a			1,4			.056
p*		- 7	2.54			.1

132300 center lead spread/3 lead lock





	MM			IN		
	min	max	fix	min	max	fix
а	7	13	17,045	.275	.511	
ь	4	10		.157	393	
0			1,4			.056
p*			2.54			3

132400 double kink on three lead - in line





MM			IN			
	min	max	fix.	min	max	fix
a	8	11		.238	.433	
ь	3	8		.118	.314	
0			1,4			.056

133100 90° BENDING CENTER LEAD OFF SET





	MM				IN		
	min	max	fix	min	max	fix	
a	3	5	200	.118	.196		
b*			5			.196	
f*			6			.216	
p		- 1	5,08			.2	